

Input Data (DC, PV)			
Number of Input MC4 Connector	1 sets		
MPPT Voltage Range	16V-48V		
Operation Voltage Range	20V-50V		
Maximum Input Voltage	50V		
Startup Voltage	22V		
Maximum Input Power	300W	350W	400W
Maximum input Current	12A	14A	16A
Output Data(AC)			
Single-Phase Grid Type	120V&230V	120V&230V	120V&230V
Rated Output Power	300W	350W	400W
Maximum Output Power	300W	350W	400W
Nominal Output Current	@120VAC:2.5A/@230VAC:1.3A @120VAC:2.9A/@230VAC:1.5A @120VAC:3.3A/@230VAC:1.7/		
Nominal Output Voltage	120VAC/230VAC		
Default Output Voltage Range	@120VAC:80V-160V/@230VAC:180V-270V		
Nominal Output Frequency	50Hz/60Hz		
Default Output Frequency Range	@50Hz:48Hz-51Hz/@60Hz:58Hz-61Hz		
Power Factor	>0.99%		
Total Harmonic Distortion	THD <5%		
Maximum Units per Branch	@120VAC:5units /@230VAC: 10units		
Efficiency			
Peak Efficiency	95%		
Nominal MPPT Efficiency	99.5%		
Night Power Consumption	<1W		
Mechanical Data			
Operating Ambient Temperature Range	-40°Cto +65°C		
Storage Temperature Range	-40°Cto +85°C		
Dimensions(W*H *D)	240mmx185mm x 45mm (not include connectors and cable)		
Weight	1.6kg		
Max Current of AC Bus Cable	20A		
Waterproof Grade	IP66		
Cooling Mode	Natural Convection- No Fans		
Other Features			
Communication	WIFI (Cloud monitoring)		
Transformer Design	High Frequency Transformers, Galvanically Isolated		
Integrated Ground	Equipment ground is provided by the PE in the AC cable. No additional ground is required		
Protection Functions	Isolated Island Protection, Voltage Protection, Frequency Protection, Temperature Protection, Current Protection, etc		

GYSMI-300W

GYSMI-350W

GYSMI-400W

Product specifications are subject to change without prior notice.

Design Compliance

Excellent low light lock function (APL) and higher conversion ef ciency.

GSMI SERIES MICRO SOLAR INVERTER

**SOLAR INVERTER** 

EN IEC61000-3-2:2019+A1:2021,EN 61000-3-3:2013+A1:2019+A2:2021, EN IEC55014-2:2021,EN IEC55014-2:2021.