

Hybrid Inverter

SUN- 3.6 / 5 / 6 K-SG03LP1-EU



-  Colorful touch LCD, IP65 protection degree
-  DC couple and AC couple to retrofit existing solar system
-  Max. 16pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
-  Max. charging/discharging current of 135A
-  6 time periods for battery charging/discharging
-  Support storing energy from diesel generator

Technical Data

Model	SUN-3.6K-SG03LP1-EU		SUN-5K-SG03LP1-EU		SUN-6K-SG03LP1-EU	
Battery Input Data						
Battery Type	Lead-acid or Li-Ion					
Battery Voltage Range (V)						
Max. Charging Current (A)	90		120		135	
Max. Discharging Current (A)	90		120		135	
External Temperature Sensor	Yes					
Charging Curve	3 Stages / Equalization					
Charging Strategy for Li-Ion Battery	Self-adaption to BMS					
PV String Input Data						
Max. DC Input Power (W)	4680		6500		7800	
Rated PV Input Voltage (V)	370 (125~500)					
Start-up Voltage (V)	125					
MPPT Voltage Range (V)	150-425					
Full Load DC Voltage Range (V)	300-425					
PV Input Current (A)	13+13					
Max. PV ISC (A)	17+17					
Number of MPPT / Strings per MPPT	2/1+1					
AC Output Data						
Rated AC Output and UPS Power (W)	3600		5000		6000	
Max. AC Output Power (W)	3690		5500		6600	
AC Output Rated Current (A)	16.4		22.7		27.3	
Max. AC Current (A)	18		25		30	
Max. Continuous AC Passthrough (A)	35				40	
Peak Power (off grid)	2 time of rated power, 10 S					
Power Factor	0.8 leading to 0.8 lagging					
Output Frequency and Voltage	50/60Hz; L/N/PE 220/230Vac (single phase)					
Grid Type	Single Phase					
DC injection current (mA)	THD<3% (Linear load<1.5%)					
Efficiency						
Max. Efficiency	97.60%					
Euro Efficiency	97.00%					
MPPT Efficiency	99.90%					
Protection						
Integrated	PV Input Lightning Protection, Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Surge protection					
Certifications and Standards						
Grid Regulation	CEI 0-21, VDE-AR-N 4105, NRS 097, IEC 62116, IEC 61727, G99, G98, VDE 0126-1-1, RD 1699, C10-11					
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2					
General Data						
Operating Temperature Range (°C)	-45~60°C, >45°C derating					
Cooling	Natural cooling					
Noise (dB)	<30 dB					
Communication with BMS	RS485; CAN					
Weight (kg)	20.5					
Size (mm)	330W x 580H x232D					
Protection Degree	IP65					
Installation Style	Wall-mounted					
Warranty	5 years					