



T1-11kW 3P IC-CPD Portable AC Charger

- TUV certification
- 6~16A Adjustable current
- Relay welding inspection
- Easy installation & maintenance
- Internal temperature detection and protection
- Scheduled & delayed charging
- Type A+DC6mA
- IP66
- PE missed alarm
- LCD+LED Indicator
- Touch button
- Three-phase mode 2

• Technical Specification

AC Power supply	It can meet 16A three-phase AC charging, and the current can be switched 6A,8A,10A,13A,16A
Charging Mode	IEC62196-2,IEC62752 CE,CB,TUV Mark,UKCA
Working power	230V+10%,50Hz±2%
Scenes	Indoor/Outdoor
Altitude (m)	≤2000
IP	IP66
Button	Current switching, cycle display,scheduled charging
Working environment temperature	-25°C~50°C
Storage temperature	-40°C~80°C
Environment humidity	< 93% > RH±3 % RH
External magnetic field	Earth's magnetic field,Not exceeding five times the earth's magnetic field in any direction
Sinusoidalwave distortion	Not exceeding 5 %
Protection	Over-current,over-voltage and under-voltage,over temperature ≥70°C, reduce to 6A to chargeand stop charging when > 75°C
Leakage protection	Type A(AC 30mA)+DC6mA
Temperature check	1.input plug cable temperature detection 2.Relay or internal temperature detection
Welding alarm	Yes, the relay fails after welding and inhibits charging
Relay control	Relay open and close
LED	Power,charging,fault three-color LED indicator
Product size(H*W*D)	257.06mmx104.36mmx60.65mm

• Product picture

