



T1-1P 2.3kW 3.0kW 3.68kW

IC-CPD Portable AC Charger

- TUV certification
- 6~16A Adjustable current
- Relay welding inspection
- Easy installation & maintenance
- Internal temperature detection and protection
- Scheduled & delayed charging
- Type A+DC6mA
- IP66
- PE missed alarm
- LCD+LED Indicator
- Touch button
- Single-phase mode 2

Technical Specification

AC Power supply	2.3kW: 6A/8A/10A	3.0kW: 6A/8A/10A/13A	3.68kW: 6A/8A/10A/13A/16A
Working power	230V+10%,50Hz±2%		
Scenes	Indoor/Outdoor		
Altitude (m)	≤2000		
IP	IP66		
Button	Current switching, cycle display, scheduled charging		
Working environment temperature	-25°C~50°C		
Storage temperature	-40°C~80°C		
Environment humidity	< 93% > RH±3 % RH		
External magnetic field	Earth's magnetic field, Not exceeding five times the earth's magnetic field in any direction		
Sinusoidal wave distortion	Not exceeding 5 %		
Protection	Over-current, over-voltage and under-voltage, over temperature ≥70°C, reduce to 6A to charge and stop charging when > 75°C		
Leakage protection	Type A (AC 30mA)+DC6mA		
Temperature check	1. input plug cable temperature detection		2. Relay or internal temperature detection
Welding alarm	Yes, the relay fails after welding and inhibits charging		
Relay control	Relay open and close		
LED	Power, charging, fault three-color LED indicator		
Product size(H*W*D)	246mmx81mmx50mm		

Product picture

