

0.03A、0.1A、0.3A
Rated residual action current

RCCB
IEC/EN 61008-1, IEC/EN 62423, GB/T 22794, GB/T 16916.1

CE CB

GYL9-F/B



GYL9-F/B residual current operated circuit breaker is suitable for AC 50/60Hz, rated voltage two poles 240V, four poles 415V, rated current up to 100A lines. Used for detecting AC leakage, pulsating DC leakage, smooth DC leakage, composite wave leakage, and high-frequency leakage up to 1kHz. When personal electric shock or circuit leakage current exceeds the specified value, the circuit breaker automatically cuts off the faulty power supply in a very short time, protecting the safety of personnel and electrical equipment. The circuit breaker can also be used for infrequent on/off operations of the line under normal circumstances.

The circuit breaker is suitable for various applications, including industrial, commercial, high-rise buildings, and residential use.

- Equipped with AC leakage, pulsating DC leakage, smooth DC leakage, composite wave leakage, and high-frequency leakage protection devices up to 1kHz - with complete protection functions
- Compliant with environmental RoHS 2.0
- Double busbar wiring function
- The product has a leakage fault indicator
- Wiring capacity: (1-35) mm²

F-type:
Type B:

Product Model And Implication

GYL9	B
Product model	Residual current action type
RCCB	F type B type

Residual leakage current breaking time

Rated current I _n (A)	Rated residual action current I _{Δn} (mA)	Residual current breaking time (s)				
		I _{Δn}	2I _{Δn}	5I _{Δn}	5A~200A	500A
16~100	30、100、300	≤0.1	≤0.08	≤0.04	≤0.04	≤0.04

Technical Specification

Rated Voltage (U _n)	230/240V、240/415V
Rated Current (I _n)	16A、20A、25A、32A、40A、50A、63A、80A、100A
Rated insulation voltage (U _i)	500V
Rated impact tolerance voltage (U _{imp})	4kV
Rated residual action current (I _{Δn})	0.03A、0.1A、0.3A
Poles	1P+N、3P+N
Residual current action type	Type B Type F
Working Frequency	50/60Hz
Rated limit short circuit current (I _{nc})	6000A、10000A
Rated limit Remaining short circuit current (I _{Δc})	6000A、10000A
Rated on and off capacity (I _m)	500A(I _n ≤50A),or 10In(I _n =63A)
Rated residual switching and breaking capacity (I _{Δm})	500A(I _n ≤50A),or 10In(I _n =63A)
Tightening moment:	2.5N·m
Class of protection:	IP20
Installation :	TH35-7.5 standard guide rail
Mechanical life:	10000 times
Electrical life:	4000 times

Outline Overall And Installing Dimensions

